



Ashirvad *Industries*



APPROVED



COMPOSITES PULTRUSION MACHINE

Reciprocating Hydraulic,
Hydraulic Actuating Two Grippers



PULTRUSION MACHINE SPECIFICATIONS

Reciprocating Hydraulic, Hydraulic Actuating Two Grippers

MODEL	AIHP-HGR-10	AIHP-HGR-12
Pulling Capacity	10000 kgf.	12000 kgf.
Product Size Width X Height (in mm)	600 X 150	800 X 150
Pulling Speed mm / min	80 - 1200	80 - 1200
Gripper Length Width	500-600 mm 300 mm	500-600 mm 300-400 mm
No. of Grippers	Double Platen	Double Platen
Heating Zone	6 - 9 [16 Amp. Each]	6 - 12 [16 Amp. Each]
Moving Puller Size Width X Length (in mm)	800 X 650	800 X 650 & 1000 X 650
Puller Stroke (in mm)	800	800
Die Clamping Area Width X Length (in mm)	1000 X 1000	1000 X 1000 & 1200 X 1000
Electrical Power Req.	6.0 kW.	9.5 kW.
Overall Dimensions L X W X H Meter (Approx)	6.2 X 1.2 X 1.6	6.2 X 1.4 X 1.6
Cut of Saw		
Blade Ø mm	400	500
Motor kW.	1.5	2.2
Compressed Air Req. @ 4.5 kg/cm ²	4 CFM	

*** Operating Options : HMI (Touch Screen) or Push Button Panel**



ASHIRVAD INDUSTRIES

Plot no. 1907, Phase-ii, G.I.D.C., Industrial Estate,
Chhatral - 382728, Dist: Gandhinagar, Gujarat, India



Tel: +91 2764 234017 | **Fax:** +91 2764 232498 | **Mobile:** +91 9825286770

E-mail: info@ashirvadind.com, kmgajjar@gmail.com | **Web:** ashirvadtechno.com, ashirvadind.com